



MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE PREPERATION AND COMPANY

Product Name Stone Primer

Intended Use To provide sound base for subsequent coatings, refer to data sheet.

Producer/Supplier **DITOMA GmbH**

> Geisnangstrasse 9 71640 Ludwigsburg

Germany

Emergency Telephone

+49-7141-990550 +49-7141-9905522 Fax E-Mail info@ditoma.de

2. HAZARDS IDENTIFICATION

Critical hazards to man and the environment: None according to EU directive 1999/45/EC.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature Water based dispersion of acrylic copolymer. **Hazardous components** none according to EU directive 1999/45/EC

4. FIRST-AID MEASURES

In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

EYE CONTACT: May cause temporary irritation. Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

SKIN CONTACT: Prolong contact may cause irritation. Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION: If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention.

5. FIRE-FIGHTING MEASURES

The latex will not burn until water has fully evaporated. For residual solids use foam, CO, or dry powders. Do not use water jet. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Fire fighters should wear self-contained breathing apparatus. Closed containers exposed to fire should be cooled with water. Do not allow run-off from fire-fighting to enter drains or water-courses.





6. ACCIDENTAL RELEASE MEASURES

Exclude non-essential personnel.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in section 8. Contain and collect spillage with non-combustible absorbent materials e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

7. HANDLING STORAGE

Handling No special precautions necessary.

Observe good housekeeping practice. Keep workplace well ventilated.

Storage Store between +5 °C and +35 °C protected from frost and direct sunlight.

Do not use storage vessels or pipework made of aluminium, copper or their

alloys.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

General protective measures

The product may contain low levels of volatile organic compounds or ammonia

which may evaporate during application and drying.

Provide good general ventilation in the workplace where the product is dried or

sprayed, local extraction is recommended.

Components with

workplace parameters none according to EU directive 1999/45/EC

Personal protective

equipment -

Respiratory protection Use approved respiratory protection such as air-supplied mask if used in enclosed

area.

Hand protection Wear chemical resisting gloves.

Eye protection Eye protection designed to protect against liquid splashes should be worn.

Skin protection Wear waterproof overalls and boots. Wash with soap and water after handling.

Hygiene measures Do not eat, drink or smoke when handling product.





9. PHYSICAL AND CHEMICAL PROPERTIES

Physical formLiquidOdourFaint esterFlash pointNon flash

Specific gravity $1.00 \pm 0.02 \text{ kgs/L}$ **Water solubility** Fully miscible

pH 8-9Viscosity @ 25 °C 85 ± 5 KU Boiling point 100 °C

10. STABILITY AND REACTIVITY

The product is stable under recommended storage conditions – see section 7

11. TOXICOLOGICAL INFORMATION

Long term experience of handling this class of product indicates no danger to health when properly handled under industrial conditions.

12. ECOLOGICAL INFORMATION

Completely miscible with water and will be progressively diluted if admitted to waterways. The base polymer is only slowly biodegraded. Low concentration unlikely to reduce sludge activity in sewage treatment. Paint will be largely absorbed on the sludge and is consequently removed from the waste water.

13. DISPOSAL CONSIDERATIONS

Not classified as hazardous waste. The paint can be coagulated and separated from the aqueous phase for landfill or incineration. The residual liquid should not be discharged to sewage treatment without prior consent.

14. TRANSPORT INFORMATION

Non hazardous

15. REGULATORY INFORMATION

Labelling according to EU directive 1999/45/EC: Not subject to labelling.

The product contains only substances which are on the European Inventory of Existing Chemical Substances (EINECS)

16. OTHER INFORMATION

Text for R phrases shown in section 3 describing each ingredient: No R phrases are present in section 3.

The information given here is to the best of our knowledge true and accurate and is provided solely for making safety assessments. It is not a sales specification or an indication of suitability for a particular use.

Revised on JULY 2010, formatted as per 1999/45/EC. This supersedes previous version dated October 2009.