

## STONE PRIMER

<b>Description</b>	An ultra fine particle size stabilizing solution based on pure acrylic copolymer formulated to penetrate into porous surfaces. It provides a sound base for subsequent coating with CoolDry cooling paint.
<b>Scope</b>	Stone Primer exhibits excellent wetting and adhesion to a wide range of substrates. It penetrates much deeper into masonry surfaces than conventional fine particle size systems. Recommended for interior and exterior; friable concrete surfaces; chalky masonry or plaster; substrates of uneven porosity.
<b>Composition</b>	Pure acrylic copolymer dispersion.
<b>Finish</b>	Smooth, clear, low sheen
<b>Colour</b>	Clear
<b>Drying time</b>	Dry within 1 hour. Re-coatable after 4 hours Checked at 25 °C and relative humidity not more than 75 %.
<b>Specific Gravity</b>	1.00 ± 0,01 kg/l
<b>% Volume solids</b>	14 ± 0.5%
<b>Spread rate</b>	10 – 12 m <sup>2</sup> /Litre (Depending on surface condition and its absorbency).
<b>Thinner/clean up</b>	Water. After use clean the equipment immediately with water.
<b>Clean up</b>	A detergent solution can be used for machine cleaning.
<b>Flash point</b>	Non flammable
<b>Pack size</b>	2.5 Litres
<b>Application</b>	Brush, roller, spray. Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95 % and condensation is likely. Only apply when surface temperature is 3 °C or more above dew point.
<b>Surface Preparation</b>	<p><b>1.1 Plaster, Concrete, Cement Render, Limestone and Brickwork</b> All surfaces should be clean and dry prior to applying Stone Primer. Freshly trowelled plaster should be allowed to dry for at least seven days.</p> <p><b>1.2 Previously Painted Masonry Surfaces</b> All paint that is soft, powdered, blistered, loose or flaking should be removed by scraping, wire brushing or sanding. The surface should be clean and dry. Lime washes and other loose bound water paints should be removed as much as possible with a dry, stiff bristle brush before Stone Primer is applied.</p> <p><b>1.3 Fungus affected areas</b> must be treated properly and allowed to dry before painting.</p>

<b>Storage</b>	Store in cool, dry places and avoid direct sunlight.	
<b>Notes</b>	Appearance of this product in the container is milky white, which transforms to clear on drying.	
<b>Disposal</b>	To be disposed as normal dispersion paint. If you are not certain, please consult local authority. <b>Do not empty into drains, sewers or other watercourses.</b>	
<b>Shelf life</b>	1 Year, when stored in original conditions.	
<b>Safety precautions</b>	Please make sure to use the product only in properly ventilated areas. Do not inhale fume or spray. Avoid contact with skin and eyes. Wear appropriate protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.	
<b>First aid</b>	<b>EYES</b>	In case of accidental splashes rinse eyes with warm water immediately and obtain medical advice.
	<b>SKIN</b>	Wash skin thoroughly with water and soap or approved industrial cleaner. DO NOT USE DISSOLVER OR THINNERS.
	<b>INGESTION</b>	In case of accidental ingestion, DO NOT INDUCE VOMITING. Get medical attention immediately.

**Disclaimer**

The information on this data sheet may not be complete and is supplied as general information only. The user is responsible to make sure that the product is suitable for the purpose which he wants to use it for. Since we do not have control over the handling of the product, the standard of surface preparation of the foundation or other terms influencing the usage of this product, we are not responsible for its performance and can not be liable for any kind of occurrences by the usage of this product, unless it is specifically approved in writing by us. The information in this data sheet may be updated or changed by us from time to time, without notice, in consideration of our experience and continuous product development.